

(19) World Intellectual Property Organization
International Bureau



1 DEC 2004


(43) International Publication Date
24 December 2003 (24.12.2003)

PCT

(10) International Publication Number
WO 03/106084 A1

- (51) International Patent Classification⁷: **B23B 27/04** **BERMINGE, Erik** [SE/SE]; S Skeppsbron 10 a 1tr, S-802 80 Gävle (SE). **OLSSON, Helena** [SE/SE]; Klintbergsgatan 13, S-803 24 Gävle (SE).
- (21) International Application Number: PCT/SE03/01013
- (22) International Filing Date: 16 June 2003 (16.06.2003) (74) Agent: **TÅQUIST, Lennart**; Sandvik AB, S-811 81 Sandviken (SE).
- (25) Filing Language: Swedish (81) Designated States (*national*): CA, CN, JP, KR, US.
- (26) Publication Language: English (84) Designated States (*regional*): Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (30) Priority Data: 0201861-2 18 June 2002 (18.06.2002) SE
- (71) Applicant (*for all designated States except US*): **SANDVIK AB** [SE/SE]; S-811 81 Sandviken (SE). Published:
— with international search report
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): **HANSSON, Per** [SE/SE]; Iggövagen 57, S-805 96 Gävle (SE). *For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: CUTTING TOOL HEAD FOR A METALWORKING TOOL



(57) Abstract: The present invention relates to a tool head for a chip metal working tool having a cutting insert (3), comprising a basic holder (1) and an integral insert holder (4), the forward portion of which is provided with an insert pocket between a lower support portion (6) and an upper clamp portion (5) wherein the upper clamp portion (5) is actuatable by a press device. The characteristic is that the press device is in the shape of a clamp screw (19) with a conical head (18) that is received in a recess in the basic holder (1) and arranged to be subjected to displacement in its axial direction such that its conical head (18) upon insertion in a slit (20) spaced from the insert pocket achieves such bending outwardly of the upper portion of the basic holder such that thanks to its movement a clamping of the insert occurs.

WO 03/106084 A1